



ATTESTATION

of conformity with European Directives

BV LCIE CHINA Number N°2566AS12BUTO59356
Product Electric Vehicle Supply Equipment
Reference See Annex 1 Model list on page 2, 3

Trademark



Issued to BEXIE GROUP S.L.
Address CALLE COVADONGA 5 – 33002 OVIEDO (ASTURIAS) SPAIN
Manufacturer BEXIE GROUP S.L.
Address CALLE COVADONGA 5 – 33002 OVIEDO (ASTURIAS) SPAIN
Technical characteristics See Annex 1 on page 2, 3

The submitted sample of the above equipment has been tested according to following European Directive and following standards:

RE Directive 2014/53/EU

Standards	Report number	Report date
Article 3.1(a) Safety: EN IEC 61851-23:2014 in conjunction with EN 61851-1:2011	BUTO-ESH-P25111600	11/24/2025
Article 3.1(a) Health: EN IEC 62311:2020, EN 50665:2017	BUTO-ESH-P25111600B-6	11/24/2025
Article 3.1(b) EMC: EN 301 489-1 V2.2.3 (2019-11) EN 301 489-3 V2.3.2 (2023-01) EN 301 489-52 V1.3.1 (2024-11) EN IEC 61851-21-2:2021	BUTO-ESH-P25111600B-2 BUTO-ESH-P25111600B-1	11/24/2025 11/24/2025
Article 3.2 Radio: EN 301 511 V12.5.1 (2017-03) EN 301 908-1 V15.2.1 (2023-01) EN 301 908-2 V13.1.1 (2020-06) EN 301 908-13 V13.2.1 (2022-02) EN 300 330 V2.1.1 (2017-02)	BUTO-ESH-P25111600B-3 BUTO-ESH-P25111600B-4 BUTO-ESH-P25111600B-5	11/24/2025 11/24/2025 11/24/2025

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.

Shanghai (P.R. China), 18th August, 2025.

Product Line Manager

Jacky Qiu

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document is related to the tested specimen of the described electrical sample.

Annex 1 Model list

Model name	Parameters of input and output	Protection class	Radio function	Mass
BXC60-D	Input: AC 380-415V, 102A, 50/60Hz, Output: 2*CCS, Maximum power 60kw, DC 150-1000V, DC 200A for each CCS2, -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	320kg
BXC90-D	Input: AC 380-415V, 152A, 50/60Hz, Output: 2*CCS, Maximum power 90kw, DC 150-1000V, DC 250A for each CCS2, -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	340kg
BXC120-D	Input: AC 380-415V, 203A, 50/60Hz, Output: 2*CCS, Maximum power 120kw, DC 150-1000V, DC 250A for each CCS2, -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	360kg
BXC120-D-350	Input: AC 380-415V, 203A, 50/60Hz, Output: 2*CCS, Maximum power 120kw, DC 150-1000V, DC 350A for each CCS2, -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	360kg
BXC60-S	Input: AC 380-415V, 102A, 50/60Hz, Output: Maximum power 60kw,	IP55 IK10 Class I	RFID 3G/4G	310kg

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.



	DC 150-1000V, DC 200A for CCS2 -30°C to 50°C			
BXC90-S	Input: AC 380-415V, 152A, 50/60Hz, Output: Maximum power 90kw, DC 150-1000V, DC 250A for CCS2 -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	330kg
BXC120-S	Input: AC 380-415V, 203A, 50/60Hz, Output: Maximum power 120kw, DC 150-1000V, DC 250A for CCS2 -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	350kg
BXC120-S-350	Input: AC 380-415V, 203A, 50/60Hz, Output: Maximum power 120kw, DC 150-1000V, DC 350A for CCS2 -30°C to 50°C	IP55 IK10 Class I	RFID 3G/4G	350kg